



Item Overview

Item#: 2T1118-2 (Inactive)

Model: [AWA2448ZDXC](#)

Condensing Unit Type: Indoor - Air Cooled

Brand/Family: AW

Application: LBP - Low Back Pressure

Refrigerant: R-404A/R-407A/R-448A/R-449A/R-452A

Voltage/Frequency: 208-230V ~ 60Hz

Compressor Type: Reciprocating

Coil Type: Tube - Fin

Specifications

Dimensions - Height:	15
Dimensions - Width:	19
Dimensions - Length:	24
Dimensions Unit of Measure:	IN
Discharge Line Size:	3/8 in (9.52mm)
Suction Line Size:	5/8 in (15.9mm)
Run Capacitor Mfd. Voltage:	35 MFD/370 Volt
Air Flow:	615 Cubic Feet per Minute
Fan Motor Quantity:	1
Pump Down Capacity:	6.3 Pounds
Design Pressure Low:	181
Design Pressure High:	450
Fan Motor RLA:	.7
Max. Fuse Size:	15
Min. Circuit Ampacity:	11.6
Fan Motor:	<input checked="" type="checkbox"/>
Liquid Filter:	<input checked="" type="checkbox"/>
Dual Pressure Control:	<input checked="" type="checkbox"/>
Defrost Timer:	<input checked="" type="checkbox"/>
Filter Drier:	<input checked="" type="checkbox"/>
Receiver:	<input checked="" type="checkbox"/>

Replacement Parts

Are you a European Customer? Please use the TParts Finder Tool for the most accurate, up-to-date replacement parts information.

[Go TO TParts](#)

Run Cap Kit:	K150-14
Relay Kit:	K71-43
Start Cap Kit:	K146-44
Compressor:	AW610EH-111-J7

Documents

[Technical Data Sheet \(EN\)](#)

[Sales Drawing \(EN\)](#)