

## Item Overview

Item#: 32L1451-6U **(Inactive)**

Model: [AWA9512ZXNLN](#)

Condensing Unit Type: Outdoor

Brand/Family: AW

Application: CBP - Commercial Back Pressure

Refrigerant: R-404A/R-407A/R-448A/R-449A/R-452A

Voltage/Frequency: 208-230V ~ 60Hz

Compressor Type: Reciprocating

Coil Type: Tube - Fin

## Specifications

Dimensions - Height:	26.08
Dimensions - Width:	36.25
Dimensions - Length:	26.43
Dimensions Unit of Measure:	IN
Discharge Line Size:	3/8 Inch Sweat
Suction Line Size:	7/8 Inch Sweat
Run Capacitor Mfd. Voltage:	35 MFD/370 Volt
Air Flow:	1750 Cubic Feet per Minute
Fan Motor Quantity:	2
Pump Down Capacity:	19.8 Pounds
Design Pressure Low:	181
Design Pressure High:	450
Fan Motor RLA:	.7
Max. Fuse Size:	25
Min. Circuit Ampacity:	14.91
Fan Motor:	<input checked="" type="checkbox"/>
Crankcase Heater:	<input checked="" type="checkbox"/>
Defrost Timer:	<input checked="" type="checkbox"/>
Filter Drier:	<input checked="" type="checkbox"/>
Receiver:	<input checked="" type="checkbox"/>

## Replacement Parts

*Are you a European Customer? Please use the TParts Finder Tool for the most accurate, up-to-date replacement parts information.*

[Go TO TParts](#)

<b>Start Cap Kit:</b>	<b>K146-44</b>
<b>Run Cap Kit:</b>	<b>K150-14</b>
<b>Relay Kit:</b>	<b>K71-62</b>
<b>Compressor:</b>	<b>AW616ET-099-J7</b>

## Documents

[Sales Drawing \(EN\)](#)  
[Technical Data Sheet \(EN\)](#)