

## Item Overview

Item#: 32L292-6C **(Inactive)**

Model: [AKA9440ZXDUS](#)

Condensing Unit Type: Outdoor

Brand/Family: AK

Application: CBP - Commercial Back Pressure

Refrigerant: R-404A/R-407A/R-448A/R-449A/R-452A

Voltage/Frequency: 208-230V ~ 60Hz

Compressor Type: Reciprocating

Coil Type: Tube - Fin

## Specifications

Dimensions - Height:	26.08
Dimensions - Width:	28.94
Dimensions - Length:	26.55
Dimensions Unit of Measure:	IN
Discharge Line Size:	3/8 Inch Sweat
Suction Line Size:	1/2 Inch Sweat
Run Capacitor Mfd. Voltage:	15 MFD/370 Volt
Air Flow:	750 Cubic Feet per Minute
Fan Motor Quantity:	1
Pump Down Capacity:	15.7 Pounds
Design Pressure Low:	181
Design Pressure High:	450
Fan Motor RLA:	.7
Max. Fuse Size:	15
Min. Circuit Ampacity:	6.46
Fan Motor:	<input checked="" type="checkbox"/>
Crankcase Heater:	<input checked="" type="checkbox"/>
Accumulator:	<input checked="" type="checkbox"/>
Suction Filter:	<input checked="" type="checkbox"/>
Filter Drier:	<input checked="" type="checkbox"/>
Receiver:	<input checked="" type="checkbox"/>

## Replacement Parts

*Are you a European Customer? Please use the TParts Finder Tool for the most accurate, up-to-date replacement parts information.*

[Go TO TParts](#)

<b>Overload Kit:</b>	<b>K90-87</b>
<b>Compressor:</b>	<b>AK175ET-037-J7</b>
<b>Start Cap Kit:</b>	<b>K146-02</b>
<b>Run Cap Kit:</b>	<b>K150-03</b>
<b>Relay Kit:</b>	<b>K71-17</b>

## Documents

[Sales Drawing \(EN\)](#)  
[Technical Data Sheet \(EN\)](#)