

This is an Inactive product and is no longer being manufactured. It may have inventory able to be purchased.



Model: AHA7480AXD (Inactive)

(AHA7480A)

Product Description

Compressor Type: Reciprocating

Application: MBP - Medium Back Pressure

Refrigerant: R-12

Voltage/Frequency: 200V ~ 50Hz / 208-230V ~ 60Hz

Version: AH Series

Specifications

General

Evaporating Temp. Range :-23.3°C to -1.1°C (-10°F to 30°F)

Motor Torque: High Start Torque (HST)

Compressor Cooling: Fan

Mechanical

Weight: 69 LB

Displacement (cc): 47.088

Oil Charge (cc): 1331

Electrical

Locked Rotor Amps (LRA): 41

Rated Load Amps (RLA 60Hz): 6.5

Voltage Range (50Hz): 180-220

Voltage Range (60Hz): 187-254

Rated Load Amps (RLA 50Hz): 0

Max. Continuous Current (MCC in Amps): 10.9

Motor Type: CSR

Agency Approval

UL_RECOGNIZED, CE_LISTED, cURus_RECOGNIZED

Performance

[See all performance data](#)

ASHRAE (R-12)

Test Voltage	230V ~ 60HZ
(R) Refrigeration Capacity (BTU/h)	8000
(R) Refrigeration Capacity (Kcal/h)	2016
(R) Refrigeration Capacity (W)	2344
Input Power (W)	1400
(E) Efficiency (BTU/Wh)	5.71
(E) Efficiency (Kcal/Wh)	1.44
(E) Efficiency (W/W)	1.67
EVAP TEMP	-6.7°C (20°F)
COND TEMP	54°C (130°F)
AMBIENT TEMP	35°C (95°F)
RETURN GAS	35°C (95°F)
LIQUID TEMP	46°C (115°F)

Item

[AH160FF-504-A4](#) (Inactive)

[AH160FF-504-J7](#) (Inactive)

[AH160FF-509-A4](#) (Inactive)

[AH160FF-509-A4Y](#) (Inactive)

[AH160FF-509-J7](#) (Inactive)