

This is an inactive product and is no longer being manufactured. It may have inventory able to be purchased.



Model: AHA7513ZXG (Inactive)

(AHA7513Z)

Product Description

Compressor Type: Reciprocating

Application: MBP - Medium Back Pressure

Refrigerant: R-404A

Voltage/Frequency: 380-420V 3~ 50Hz / 460V 3~ 60Hz

Version: AH Series

Specifications

General

Evaporating Temp. Range :-23.3°C to -1.1°C (-10°F to 30°F)

Motor Torque: High Start Torque (HST)

Compressor Cooling: Fan

Mechanical

Weight: 78 LB

Displacement (cc): 49.055

Oil Charge (cc): 1331

Electrical

Locked Rotor Amps (LRA): 24

Rated Load Amps (RLA 60Hz): 3.9

Voltage Range (50Hz): 342-462

Voltage Range (60Hz): 414-506

Rated Load Amps (RLA 50Hz): 0

Max. Continuous Current (MCC in Amps): 8.1

Motor Type: 3PH

Agency Approval

cURus_RECOGNIZED

Performance

[See all performance data](#)

ARI

Test Voltage	460V 3~ 60HZ
(R) Refrigeration Capacity (BTU/h)	13250
(R) Refrigeration Capacity (Kcal/h)	3339
(R) Refrigeration Capacity (W)	3882
Input Power (W)	2600
(E) Efficiency (BTU/Wh)	5.1
(E) Efficiency (Kcal/Wh)	1.28
(E) Efficiency (W/W)	1.49
EVAP TEMP	-6.7°C (20°F)
COND TEMP	49°C (120°F)
AMBIENT TEMP	35°C (95°F)
RETURN GAS	4.4°C (40°F)
LIQUID TEMP	49°C (120°F)

Item

AH245TF-503-A4 (Inactive)

AH245TF-508-A4 (Inactive)