

# Model: AJB4461AXA (Inactive)

### **Product Description**

Compressor Type: Reciprocating

Application: HBP - High Back Pressure

Refrigerant: R-12

Voltage/Frequency: 100V ~ 50Hz / 115V ~ 60Hz

Version: AJ Series

# **Specifications**

### General

**Evaporating Temp. Range :**-6.7°C to 12.8°C (20°F to 55°F)

**Motor Torque:** High Start Torque (HST)

Compressor Cooling: Fan

#### Mechanical

Weight: 50 LB

**Displacement (cc):** 18.092 **Oil Type:** Synthetic Alkylate

Viscosity (cSt): 32 Oil Charge (cc): 664

#### Electrical

Locked Rotor Amps (LRA): 45

Rated Load Amps (RLA 60Hz): 9.5

Voltage Range (50Hz): 90-110 Voltage Range (60Hz): 103-127

Rated Load Amps (RLA 50Hz): 0

Max. Continuous Current (MCC in Amps): 0

Motor Resistance (Ohm) - Main: 0.8 Motor Resistance (Ohm) - Start: 4.79

Motor Type: CSIR Agency Approval

cURus\_RECOGNIZED

# Performance

#### See all performance data

### ASHRAE (R-12)

Test Voltage 115V ~ 60HZ

(R) Refrigeration Capacity (BTU/h) 6100

(R) Refrigeration Capacity (Kcal/h) 1537

(R) Refrigeration Capacity (W) 1787

Input Power (W)W 880

(E) Efficiency (BTU/Wh) 6.93

(E) Efficiency (Kcal/Wh) 1.75

(E) Efficiency (W/W) 2.03

EVAP TEMP 7.2°C (45°F)

COND TEMP 54°C (130°F)

AMBIENT TEMP 35°C (95°F)

RETURN GAS 35°C (95°F)

LIQUID TEMP 46°C (115°F)

Item		
AJ4	120AT-141-D4 (Inactive)	