

This is an inactive product and is no longer being manufactured. It may have inventory able to be purchased.



Model: AKA5512EDS (Inactive)

(AK5512ES)

Product Description

Compressor Type: Reciprocating

Application: HBP/AC - Air Conditioning

Refrigerant: R-22

Voltage/Frequency: 115-127V ~ 60Hz

Version: AK Series

Specifications

General

Evaporating Temp. Range :-23.3°C to 12.8°C (-10°F to 55°F)

Compressor Cooling: Fan

Mechanical

Displacement (cc): 0

Oil Charge (cc): 0

Electrical

Locked Rotor Amps (LRA): 0

Rated Load Amps (RLA 60Hz): 0

Rated Load Amps (RLA 50Hz): 0

Max. Continuous Current (MCC in Amps): 0

Motor Resistance (Ohm) - Main: 0.546

Motor Resistance (Ohm) - Start: 7.3

Performance

[See all performance data](#)

ASHRAE

Test Voltage	127V ~ 60HZ
(R) Refrigeration Capacity (BTU/h)	12000
(R) Refrigeration Capacity (Kcal/h)	3024
(R) Refrigeration Capacity (W)	3517
Input Power (W)W	1426
(E) Efficiency (BTU/Wh)	8.42
(E) Efficiency (Kcal/Wh)	2.12
(E) Efficiency (W/W)	2.47
EVAP TEMP	7.2°C (45°F)
COND TEMP	54°C (130°F)
AMBIENT TEMP	35°C (95°F)
RETURN GAS	18.3°C (65°F)
LIQUID TEMP	46°C (115°F)

Item

10591580 (Inactive)

10591605 (Inactive)

14946115 (Inactive)