This is an Inactive product and is no longer being manufactured. It may have inventory able to be purchased.

Model: AVD5535EXN (Inactive)

Product Description

Compressor Type: Reciprocating

Application: HBP/AC - Air Conditioning

Refrigerant: R-22

Voltage/Frequency: 200-220V ~ 50Hz / 208-230V ~ 60Hz

Version: AV Series

Specifications

General

Evaporating Temp. Range :-23.3°C to 12.8°C (-10°F to 55°F)

Motor Torque: Low Start Torque (LST)

Compressor Cooling: Fan

Mechanical

Weight: 82 LB

Displacement (cc): 59.685

Oil Type: Synthetic Alkylate

Viscosity (cSt): 32

Oil Charge (cc): 1624

Electrical

Locked Rotor Amps (LRA): 92

Rated Load Amps (RLA 60Hz): 13.8

Voltage Range (50Hz): 180-242

Voltage Range (60Hz): 197-254

Rated Load Amps (RLA 50Hz): 0

Max. Continuous Current (MCC in Amps): 27.3

Motor Resistance (Ohm) - Main: 0.522

Motor Resistance (Ohm) - Start: 1.27

Motor Type: PTCS_CR

Agency Approval

cURus_RECOGNIZED

Performance

See all performance data

ARI	
Test Voltage	230V ~ 60HZ
(R) Refrigeration Capacity (BTU/h)	35500
(R) Refrigeration Capacity (Kcal/h)	8946
(R) Refrigeration Capacity (W)	10402
Input Power (W)W	3135
(E) Efficiency (BTU/Wh)	11.32
(E) Efficiency (Kcal/Wh)	2.85
(E) Efficiency (W/W)	3.32
EVAP TEMP	7.2°C (45°F)
COND TEMP	54°C (130°F)
AMBIENT TEMP	35°C (95°F)
RETURN GAS	18.3°C (65°F)
LIQUID TEMP	46°C (115°F)

Item

AV126ET-041-A4 **(Inactive)**

AV126ET-041-B4 **(Inactive)**

AV126ET-041-C4 **(Inactive)**