

This is an Inactive product and is no longer being manufactured. It may have inventory able to be purchased.



Model: AWG5532EXC (Inactive)

Product Description

Compressor Type: Reciprocating

Application: HBP/AC - Air Conditioning

Refrigerant: R-22/R-407C

Voltage/Frequency: 220-240V ~ 50Hz

Version: AW Series

Specifications

General

Evaporating Temp. Range :-23.3°C to 12.8°C (-10°F to 55°F)

Motor Torque: Low Start Torque (LST)

Compressor Cooling: Fan

Mechanical

Weight: 70 LB

Displacement (cc): 54.293

Oil Type: Polyolester

Viscosity (cSt): 32

Oil Charge (cc): 1141

Electrical

Locked Rotor Amps (LRA): 83

Rated Load Amps (RLA 60Hz): 0

Voltage Range (50Hz): 198-264

Rated Load Amps (RLA 50Hz): 12.7

Max. Continuous Current (MCC in Amps): 21

Motor Resistance (Ohm) - Main: 0.82

Motor Resistance (Ohm) - Start: 2.54

Motor Type: PSC

Agency Approval

CE_LISTED, cURus_RECOGNIZED

Performance

[See all performance data](#)

ARI (R-22)

Test Voltage	220V ~ 50HZ
(R) Refrigeration Capacity (BTU/h)	25500
(R) Refrigeration Capacity (Kcal/h)	6426
(R) Refrigeration Capacity (W)	7472
Input Power (W)	2660
(E) Efficiency (BTU/Wh)	9.59
(E) Efficiency (Kcal/Wh)	2.42
(E) Efficiency (W/W)	2.81
EVAP TEMP	7.2°C (45°F)
COND TEMP	54°C (130°F)
AMBIENT TEMP	35°C (95°F)
RETURN GAS	18.3°C (65°F)
LIQUID TEMP	46°C (115°F)

Item

AW708KT-093-A4 (Inactive)

AW708KT-094-A4 (Inactive)

AW708KT-096-A4 (Inactive)

AW708KT-104-A4 (Inactive)

AW714KT-101-B4 (Inactive)

AW721KT-103-A4 (Inactive)

AW721KT-104-A4 (Inactive)