

This is an inactive product and is no longer being manufactured. It may have inventory able to be purchased.



Model: AZA1340DTS (Inactive)

(AZ1340DS)

Product Description

Compressor Type: Reciprocating

Application: LBP - Low Back Pressure

Refrigerant: R-12

Voltage/Frequency: 115V ~ 60Hz

Version: AZ Series

Specifications

General

Evaporating Temp. Range :-34.4°C to -12.2°C (-30°F to 10°F)

Motor Torque: Low Start Torque (LST)

Compressor Cooling: Static

Mechanical

Weight: 7 KG

Displacement (cc): 4

Oil Type: Synthetic Alkylate

Viscosity (cSt): 32

Oil Charge (cc): 263

Electrical

Locked Rotor Amps (LRA): 18.8

Rated Load Amps (RLA 60Hz): 1.95

Voltage Range (60Hz): 92-127

Rated Load Amps (RLA 50Hz): 1.95

Max. Continuous Current (MCC in Amps): 0

Motor Resistance (Ohm) - Main: 2.69

Motor Resistance (Ohm) - Start: 9.62

Motor Type: RSIR

Performance

[See all performance data](#)

ASHRAE

Test Voltage	115V ~ 60HZ
(R) Refrigeration Capacity (BTU/h)	410
(R) Refrigeration Capacity (Kcal/h)	103
(R) Refrigeration Capacity (W)	120
Input Power (W)	120
(E) Efficiency (BTU/Wh)	3.42
(E) Efficiency (Kcal/Wh)	.86
(E) Efficiency (W/W)	1
EVAP TEMP	
COND TEMP	
AMBIENT TEMP	
RETURN GAS	
LIQUID TEMP	

Item

[10591976](#) (Inactive)

[10591980](#) (Inactive)