

This is an inactive product and is no longer being manufactured. It may have inventory able to be purchased.



**Model: RKA5515CXV (Inactive)**

### Product Description

Compressor Type: Rotary

Application: HBP/AC - Air Conditioning

Refrigerant: R-407C

Voltage/Frequency: 265V ~ 60Hz

Version: RK Series

# Specifications

## General

**Evaporating Temp. Range** :-23.3°C to 12.8°C (-10°F to 55°F)

**Motor Torque:** Low Start Torque (LST)

**Compressor Cooling:** Fan

## Mechanical

**Weight:** 28 LB

**Displacement (cc):** 21.354

**Oil Type:** Polyvinylether

**Viscosity (cSt):** 69

**Oil Charge (cc):** 433

## Electrical

**Locked Rotor Amps (LRA):** 32

**Rated Load Amps (RLA 60Hz):** 5.3

**Voltage Range (60Hz):** 239-292

**Rated Load Amps (RLA 50Hz):** 0

**Max. Continuous Current (MCC in Amps):** 9

**Motor Resistance (Ohm) - Main:** 2.24

**Motor Resistance (Ohm) - Start:** 4.86

**Motor Type:** PSC

## Agency Approval

**cURus\_RECOGNIZED**

## Performance

[See all performance data](#)

### ASHRAE (R-407C)

Test Voltage	265V ~ 60HZ
(R) Refrigeration Capacity (BTU/h)	14400
(R) Refrigeration Capacity (Kcal/h)	3631
(R) Refrigeration Capacity (W)	4220
Input Power (W)	1375
(E) Efficiency (BTU/Wh)	10.48
(E) Efficiency (Kcal/Wh)	2.64
(E) Efficiency (W/W)	3.07
EVAP TEMP	7.2°C (45°F)
COND TEMP	54°C (130°F)
AMBIENT TEMP	35°C (95°F)
RETURN GAS	35°C (95°F)
LIQUID TEMP	46°C (115°F)

Item

**RK222KB-009-A4 (Inactive)**