



Model: RKA5518EXV (Inactive)

Product Description

Compressor Type: Rotary

Application: HBP/AC - Air Conditioning

Refrigerant: R-22

Voltage/Frequency: 265V ~ 60Hz

Version: RK Series

Specifications

General

- Evaporating Temp. Range :-23.3°C to 12.8°C (-10°F to 55°F)
- Motor Torque: Low Start Torque (LST)
- Compressor Cooling: Fan

Mechanical

- Weight: 28 LB
- Displacement (cc): 24.367
- Oil Type: Synthetic Alkylate
- Viscosity (cSt): 53
- Oil Charge (cc): 356

Electrical

- Locked Rotor Amps (LRA): 32
- Rated Load Amps (RLA 60Hz): 6.3
- Voltage Range (60Hz): 239-292
- Rated Load Amps (RLA 50Hz): 0
- Max. Continuous Current (MCC in Amps): 10
- Motor Resistance (Ohm) - Main: 2.24
- Motor Resistance (Ohm) - Start: 4.86
- Motor Type: PSC

Agency Approval

- CE_LISTED, cURus_RECOGNIZED

Performance

[See all performance data](#)

ARI (R-22)

Test Voltage	265V ~ 60HZ
(R) Refrigeration Capacity (BTU/h)	17500
(R) Refrigeration Capacity (Kcal/h)	4410
(R) Refrigeration Capacity (W)	5128
Input Power (W)W	1630
(E) Efficiency (BTU/Wh)	10.74
(E) Efficiency (Kcal/Wh)	2.71
(E) Efficiency (W/W)	3.15
EVAP TEMP	7.2°C (45°F)
COND TEMP	54°C (130°F)
AMBIENT TEMP	35°C (95°F)
RETURN GAS	18.3°C (65°F)
LIQUID TEMP	46°C (115°F)

Item

14944425 (Inactive)

RK233JB-009-A4 (Inactive)

RK233JB-009-B4 (Inactive)

RK233JB-009-S7 (Inactive)

RK233JH-022-B4 (Inactive)

RK233JL-009-B4 (Inactive)

RK233JL-022-B4 (Inactive)