

This is an Inactive product and is no longer being manufactured. It may have inventory able to be purchased.

Model: TPA2411ZAA (Inactive)

Product Description

Compressor Type: Reciprocating

Application: LBP - Low Back Pressure

Refrigerant: R-404A

Voltage/Frequency: 115V ~ 60Hz

Version: TP Series

Specifications

General

Evaporating Temp. Range : -40°C to -10°C (-40°F to 14°F)

Motor Torque: High Start Torque (HST)

Compressor Cooling: Fan

Mechanical

Weight: 30 LB

Displacement (cc): 7.276

Oil Type: Polyolester

Viscosity (cSt): 32

Oil Charge (cc): 247.67

Electrical

Locked Rotor Amps (LRA): 31

Rated Load Amps (RLA 60Hz): 4.3

Voltage Range (60Hz): 103-127

Rated Load Amps (RLA 50Hz): 0

Max. Continuous Current (MCC in Amps): 7.2

Motor Resistance (Ohm) - Main: 1.31

Motor Resistance (Ohm) - Start: 5.77

Motor Type: CSIR

Agency Approval

cURus_RECOGNIZED

Performance

[See all performance data](#)

ARI (R-404A)

Test Voltage	115V ~ 60HZ
(R) Refrigeration Capacity (BTU/h)	1119
(R) Refrigeration Capacity (Kcal/h)	282
(R) Refrigeration Capacity (W)	328
Input Power (W)	350
(E) Efficiency (BTU/Wh)	3.2
(E) Efficiency (Kcal/Wh)	.81
(E) Efficiency (W/W)	.94
EVAP TEMP	-23°C (-10°F)
COND TEMP	49°C (120°F)
AMBIENT TEMP	35°C (95°F)
RETURN GAS	4.4°C (40°F)
LIQUID TEMP	49°C (120°F)

Item

TP229AR-300-A2KO (Inactive)

TP229AR300A4KO (Inactive)

TP229AR-300-A4KO (Inactive)

TP229AR-300-A4KX (Inactive)

TP229AR-300-J7 (Inactive)