



: VS2510Z-NA9A

: -40°C to 0°C (-40°F to 32°F)

: High Start Torque (HST)

: Fan

: 42

: Polyolester

: 32

: 1400

: 76

: 13.6

: 187-254

: 0

: 24

: 0.67

: 1.519

: CSR

,

**ARI (R-404A)**

230V ~ 60HZ  
9336  
2353  
2735  
2374  
3.93  
.99  
1.15  
-6.7°C (20°F)  
49°C (120°F)  
35°C (95°F)  
4.4°C (40°F)  
49°C (120°F)

**ARI (R-449A)**

230V ~ 60HZ  
9387  
2366  
2750  
2451  
3.83  
.97  
1.12  
-6.7°C (20°F)  
49°C (120°F)  
35°C (95°F)  
4.4°C (40°F)  
49°C (120°F)

**ARI (R-452A)**

230V ~ 60HZ  
9383  
2365  
2749  
2355  
3.98  
1  
1.17  
-6.7°C (20°F)  
49°C (120°F)  
35°C (95°F)  
4.4°C (40°F)  
49°C (120°F)

**ASHRAE (R-404A)**

230V ~ 60HZ  
8451  
2130  
2476  
2645  
3.2  
.81  
.94  
-23°C (-10°F)  
54°C (130°F)  
32°C (90°F)  
32°C (90°F)  
32°C (90°F)

**ASHRAE (R-449A)**

230V ~ 60HZ  
8848  
2230  
2592  
2752  
3.22  
.81  
.94  
-23°C (-10°F)

**ASHRAE (R-452A)**

230V ~ 60HZ  
8589  
2164  
2517  
2611  
3.29  
.83  
.96  
-23°C (-10°F)

**ASHRAE (R-449A)**

54°C (130°F)

32°C (90°F)

32°C (90°F)

32°C (90°F)

**ASHRAE (R-452A)**

54°C (130°F)

32°C (90°F)

32°C (90°F)

32°C (90°F)

